

LANTERN



Product Dimension

Features:





- Classical design of lantern
- Galvanized steel plate after joining and welding of body
- Mechanical and chemical anti-corrosion treatment, UV resistant exterior painting system
- Optics: Anodized aluminum reflector and PMMA diffuser



产品技术参数表

Product Specification

Product Code	BD-550020L	BD-550024L
Input Wattage	20W	24W
LED quantity	12	12
Color Temperature	3000-6500K	3000-6500K
Luminous Flux	2890Lm ±5%	3468Lm ±5%
Input Voltage	AC100-277V	AC100-277V
Frequency Range	50/60Hz	50/60Hz
Power Factor	PF ≥ 0.9	PF ≥ 0.9
color rendering index	Ra ≥ 70	Ra ≥ 70
Temperature of Working Condition	-40--50℃	-40--50℃
Humidity of Working Condition	20%-90%	20%-90%
LED Lifetime	100000h	100000h
Protectin Grade	IP66	IP66
Installation Pipe Diameter	Φ 48mm/Φ 60mm	Φ 48mm/Φ 60mm
Installation Height	4-6m	4-6m
Net Weight	5.50kg	5.50kg
Gross Weight	6.50kg	6.50kg
Packing Size	675*310*155mm	675*310*155mm



The luminaire is equipped with multi-level dimmable power supply with interface device to remote control systems with standard protocols (DALI - 1-10V)

Packing size is outer size of box.
 elers are measured at 25℃ ambient,35% humidity experimental environment