


MINK




Physical Dimension.

Features:

- The Modern and fashionable design, it's a nice scene of garden and city.
- High efficient integrated heat radiation design, Electrostatic powder painting high strength anti-corrosion, long life span.
- High efficient LED chips and LED power supply, reasonable light distribution technology, make the lamp more high performance and practicality.
- High transparent toughened glass, high transmittance, high strength, impact resistance.

Product Specification

Product Code	BD-550033M	BD-550036M	BD-550050M
Input Wattage	33W	36W	50W
LED quantity	12	12	24
Color Temperature	3000-6500K	3000-6500K	3000-6500K
Luminous Flux	4719Lm ±5%	5220Lm ±5%	7000Lm ±5%
Input Voltage	AC100-277V	AC100-277V	AC100-277V
Frequency Range	50/60Hz	50/60Hz	50/60Hz
Power Factor	PF ≥ 0.9	PF ≥ 0.9	PF ≥ 0.9
color rendering index	Ra ≥ 70	Ra ≥ 70	Ra ≥ 70
Temperature of Working Condition	-40--50℃	-40--50℃	-40--50℃
Humidity of Working Condition	20%-90%	20%-90%	20%-90%
LED Lifetime	100000h	100000h	100000h
Protectin Grade	IP66	IP66	IP66
Installation Pipe Diameter	φ 48mm/φ 60mm	φ 48mm/φ 60mm	φ 48mm/φ 60mm
Installation Height	4-6m	4-6m	6-8m
Net Weight	5.50kg	5.50kg	5.50kg
Gross Weight	6.50kg	6.50kg	6.50kg
Packing Size	675*310*155mm	675*310*155mm	675*310*155mm



The luminaire is equipped with multi-level dimmable power supply with interface device to remote control systems with standard protocols (DALI - 1-10V)